

LUXLINE QUAD RECESSED/SURFACE



600mm x 600mm

- Sheet steel housing
- Opal PMMA diffuser
- 3MacAdam (3SDCM)
- Ambient Temp: -20° ~ +40°
- Excellent luminous uniformity over diffuser surface
- Power factor 0.9




RECESSED


CAT NO.	DRIVER	CCT	LUMINAIRE LUMENS	WATTAGE	EFFICACY Llm/W	RATED LIFE
LLQR66W24S40	Standard	4000K	2400	20W	120	L80/B20
LLQR66W24D40	DALI	4000K	2400	20W	120	L80/B20
LLQR66W22S30	Standard	3000K	2160	20W	108	L80/B20
LLQR66W22D30	DALI	3000K	2160	20W	108	L80/B20
LLQR66W30S40	Standard	4000K	3000	25W	120	L80/B20
LLQR66W30D40	DALI	4000K	3000	25W	120	L80/B20
LLQR66W27S30	Standard	3000K	2700	25W	108	L80/B20
LLQR66W27D30	DALI	3000K	2700	25W	108	L80/B20
LLQR66W36S40	Standard	4000K	3550	30W	118	L80/B20
LLQR66W36D40	DALI	4000K	3550	30W	118	L80/B20
LLQR66W32S30	Standard	3000K	3220	30W	107	L80/B20
LLQR66W32D30	DALI	3000K	3220	30W	107	L80/B20
LLQR66W41S40	Standard	4000K	4100	35W	117	L80/B20
LLQR66W41D40	DALI	4000K	4100	35W	117	L80/B20
LLQR66W37S30	Standard	3000K	3700	35W	106	L80/B20
LLQR66W37D30	DALI	3000K	3700	35W	106	L80/B20

SURFACED


CAT NO.	DRIVER	CCT	LUMINAIRE LUMENS	WATTAGE	EFFICACY Llm/W	RATED LIFE
LLQS66W24S40	Standard	4000K	2400	20W	120	L80/B20
LLQS66W24D40	DALI	4000K	2400	20W	120	L80/B20
LLQS66W22S30	Standard	3000K	2160	20W	108	L80/B20
LLQS66W22D30	DALI	3000K	2160	20W	108	L80/B20
LLQS66W30S40	Standard	4000K	3000	25W	120	L80/B20
LLQS66W30D40	DALI	4000K	3000	25W	120	L80/B20
LLQS66W27S30	Standard	3000K	2700	25W	108	L80/B20
LLQS66W27D30	DALI	3000K	2700	25W	108	L80/B20
LLQS66W36S40	Standard	4000K	3550	30W	118	L80/B20
LLQS66W36D40	DALI	4000K	3550	30W	118	L80/B20
LLQS66W32S30	Standard	3000K	3220	30W	107	L80/B20
LLQS66W32D30	DALI	3000K	3220	30W	107	L80/B20
LLQS66W41S40	Standard	4000K	4100	35W	117	L80/B20
LLQS66W41D40	DALI	4000K	4100	35W	117	L80/B20
LLQS66W37S30	Standard	3000K	3700	35W	106	L80/B20
LLQS66W37D30	DALI	3000K	3700	35W	106	L80/B20



LUCECO




This luminaire contains built-in LED lamps.



LED

The lamps cannot be changed in the luminaire.

874/2012 

STANDARDS

EN 60598-1	Luminaires - General requirements
EN 60598-2-2	Luminaires - Recessed
EN 60598-2-22	Luminaires - Emergency
EN 61347-1	Lamp controlgear - Part 1: General and safety requirements
EN 61347-2-13	Lamp controlgear - Part 2-13 : Particular requirements for d.c. or a.c. supplied electronic controlgear for LED modules
EN 55015	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
EN 61547	Equipment for general lighting purposes - EMC immunity requirements
EN 61000-3-2	Electromagnetic compatibility (EMC) - Part 3-2: Limits - for harmonic current emissions
EN 62471	Photobiological safety of lamps and lamp systems
2002/96/EC	Waste Electrical & Electronic Equipment (WEEE)
2011/65/EU	Restriction of the use of certain Hazardous Substances in EEE (RoHS)
(EC) No 1907/2006	The Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)



RoHS



